



KEGON

4" LED SURFACE MOUNT CYLINDER

BUILD YOUR CODE

KEGON							
PRODUCT	LUMENS	LED COLOR	CRI	BEAM SPREAD	VOLTAGE	HOUSING COLOR	DIMMING OPTION
KEGON	06 6250 LM (9W)	27 2700 K	80 80 CRI	SP 15°	1 120V	WH RAL 9016 white	ADIM 0-10V 5%
	12 1200 LM (9W)	30 3000 K	90 90 CRI	NFL 25°		BK RAL 9005 black	TRIAC Triac dim. Line voltage dim.*
	18 1800 LM (15W)	35 3500 K		FL 38°		+ Custom finish	DALI DALI
	20 2000 LM (15W)	40 4000 K		WFL 60°			— None
	*custom lumen output available on request			*93% efficacy			*standard option



MADE IN 

ON LIGHT

BRUMBERG

MOUNTING OPTION <i>Order as separately</i>
AP Adapter plate with different finishes then cylinder
ACM10 10ft aircraft cable mount
S10 10ft suspension set*
*Aircraft cable is combined inside power cord, designed for sleek and simple installation.

DIMENSIONS

ON LIGHT CHEAT SHEET :

*dimension are in mm



Weight trim: 3 lb (1.4 kg)

Height: 5-1/8" (130mm)

Diameter: 4-1/4" (108mm)

- Nominal Efficacy : up to 140 LM/W.
- Dry & Damp location Ingress protection IP20. Applications in wet locations will void warranty.
- Lumen maintenance L80/B10 : 50 000h at 25°C.
- Lumen maintenance for LED's tested by LED chip manufacturer in accordance with IESNA LM80-08.
- 5-year warranty on LED light engine, driver and all lighting fixture components.
- Input class 2: 15W / 120V.
- Installation for Damp & dry location only : IP54
- Die-cast aluminum housing construction.
- Certified to US and Canadian safety standards.
- Roughed textured powder-coated paint finish.
- Octogonal junction box installation.
- Luminaires are assembled in Beloeil, Canada.

DELIVERED LUMEN <i>Nominal value at 3500K & 84 CRI</i>															
CCT OPTION	2700K	2700K	2700K	3000K	3000K	3000K	3500K	3500K	3500K	4000K	4000K	4000K	Bread	Meat	Fish
CRI OPTION	80	90	97	80/A	90	97	84	90	A/80	84	90	A/80	80	80	80
MULTIPLIER	.93	.77	.67	.96	.80	.71	1	.83	.78	1.0	0.86	.83	.86	.53	1

Last update 1/13/2024

Due to continuous improvements, the information herein may be changed without notice