Eclairage On Light

SPECIFICATION SHEET

QUANTITIES:

5-1/8" x 5-1/8" LED ADJUSTBLE SURFACE MOUNT SQUARE CYLINDER

P/N: 88528073

• 3000K, CRI 80 different CCT/CRI available on request

- · 30W/2700LM custom lumen output available on request
- 40° beam spread
- Adjustability : swiveling angle 90° head adjustable : 180°
- Ingress protection IP20. For dry location only
- Die-cast aluminum housing construction
- White roughed textured powder-coated paint finish
- · Luminaires are assembled in Beloeil, Canada
- Custom color available on request

BRUMBERG



DIMENSIONS

Weight trim:

Large & Lenght:

Last update October, 2020

4-1/4" (107mm)

5-1/8"x 5-1/8" (130x130mm)

Heigth:

TECHNICAL PRODUCT SPECIFICATIONS

Type :

Project:

- Nominal Efficacy : up to 90 LM/W.
- LED source 3000K/CRI80.
- 30W/2700LM direct light.
- Ingress protection IP20.
- Lumen maintenance L80/B10 : 50 000h at 25°C.
- Lumen maintenance for LED's tested by LED chip manufacturer in accordance with IESNA LM80-08.
- 5-year warranty on LED light engine, driver and all lighting fixture components.
- Input class 2: 30W / 120V.
- Die-cast aluminum housing construction.
- Rated for dry locations only. Applications in wet locations will void warranty.
- Certified to US and Canadian safety standards.
- White Roughed textured powder-coated paint finish.
- Surface mount luminaire on standard octagonal box.
- Different LED color or finish available on request.
- Application : Residential & high end residential.
- Luminaires are assembled in Beloeil, Canada.

Due to continuous improvements, the information herein may be changed without notice

Eclairage On Light • 160-2150 Rue Pierre-Louis Le Tourneux • Beloeil • QC • J3G 0R5 • Canada • Phone 1 844 864 1212 • info@onlight.ca • www.onlight.ca