



The profile UA, UD OR UI stands out due to its versatile areas of application.
Made from high quality materials, the products convince with their functional design

KOOLED UA UD UI LED LINEAR PROFILE



BUILD YOUR CODE									
PRODUCT	LENGTH	LED	COLOR TEMP	CRI	COVER	HOUSING COLOR	ELECTRICAL OUTLET	POWER CORD LENGTH	
UA 7/8" x 3/8" (22mm x 10mm)	_____in or mm	8F 8W/M (2.4W/FT) LED FLEX ¹	27 2700 K	90 90 CRI	CF Clear flat	AN Natural anodized	S Side 	3 3FT	5 5FT
		14F 14W/M (4.4W/FT) LED FLEX ¹	30 3000 K	95 95 CRI ²	CR Clear round	BKAN Black anodized			
UD 1/2" x 1/16" (22mm x 9mm)		14F+ 14W/M (4.4W/FT) LED FLEX ¹	35 3500 K	A A Classe	FF Frosted flat ³	WH White finish RAL 9016	EN End 	8 8FT	10 10FT
		IP14F 14W/M (4.4W/FT) IP65 LED FLEX ¹	40 4000 K	FR Frosted round diffusor ³	BK Black finish RAL 9005				
UI 7/8" x 5/8" (22mm x 17mm)		19F 19.3W/M (5.8W/FT) LED FLEX ¹	50 5000 K		SD Frosted Square diffusor ³	_____ Custom color		15 15FT	20 20FT
		25F 25W/M (7.7W/FT) LED FLEX ¹		BD Frosted ballon diffusor ⁴	_____ Custom anodized	25 25FT			
					WW Wall wash lens				

Power cord color	MOUNTING	AIRCRAFT CABLE END FIXING (optional)
G Grey (standard)	SM Surface mount	RC3 2-3/4" round canopy White finish
B Black	S5 Suspension 5'	RC2 2-3/4" round canopy Black finish
W White	S10 Suspension 10'	RC1 2-3/4" round canopy Brushed aluminum finish
C Clear	S15 Suspension 15'	SC3 2-3/4" square canopy White finish
	S20 Suspension 20'	SC2 2-3/4" square canopy Black finish
	_____ Custom arm	SC1 2-3/4" square canopy Brushed aluminum finish
		BB14 Top Hat Barrel
		EY90*G 90 Eyelet

BUILD YOUR CODE			
REMOTE DRIVER: Order as separate part number.	DRIVER DIMMING	VOLTAGE	QTY
DRVR-PROFILE 24VDC / 100W ⁵	ADIM 0-10V 10%	— 120-277V*	
DRVR-PROFILE-150 24VDC / 150W	— None	*standard	
DRVR-PROFILE-IP67 24VDC / 96W IP67			




Surface mount Bracket

TECHNICAL PRODUCT SPECIFICATIONS: see back side for dimensions

- Nominal Efficacy : 108.8 lm/W with 8W/M LED Flex, 261lm/ft.
- Nominal Efficacy : 103.6 lm/W with 14W/M LED Flex, 435lm/ft.
- Nominal Efficacy : 103.6 lm/W with 14W/M LED+ Flex, 655lm/ft.
- Nominal Efficacy : 103.6 lm/W with 19.3W/M LED Flex, 700lm/ft.
- Nominal Efficacy : 124.8 lm/W with 24W/M LED Flex, 914 lm/ft.
- IP65 LED flex rated for wet location.
- Reported Life : 50'000 hrs. in accordance with IESNA TM-21-11.
- Lumen maintenance for luminaire LED's tested by LED chip manufacturer in accordance with IESNA LM80-08.
- 5-year warranty on LED light engine, driver and all lighting fixture components.
- LED flex min. cutting increment: 2" (5cm)
- Kooled LED profile made of aluminum extrusion. User-friendly pattern assembly system.
- Dimming 0-10V down to 10%
- Input : 24V DC
- Assembled/made in Canada

¹Cutting increment: 2" (5 cm). ³30% Typical luminous flux reduction
²15% Typical luminous flux reduction ⁴Only available with UD extrusion



The profile UA, UD OR UI stands out due to its versatile areas of application.

The angle of the profile is adjustable thanks to the round design.

Made from high quality materials, the products convince with their functional design

KOOLED UA UD UI LED LINEAR PROFILE

DIMENSIONS		
KOOLED UA	KOOLED UD	KOOLED UI
Weigth: 0.13lb/ft Height : 7/8" (22mm) Height : 1/2" (9.8mm) Height : 5/8" (16.8mm) Wide : 7/8" (22mm) Max Length : 20' (6m)	Weigth: 0.07lb/ft Height : 1/2" (9mm) Height : 1" (21.8mm) Wide : 1-1/16" (14.5mm) Max Length : 20' (6m)	Weigth: 0.19lb/ft Height : 7/8" (22mm) Height : 1/2" (9.8mm) Height : 5/8" (16.8mm) Wide : 7/8" (22mm) Max Length : 20' (6m)

LIGHT DISTRIBUTION

